

In the Claims:

Please amend the following claims:

1. (Previously Presented) A medical protection sheeting formed from a low frictional material having a coefficient of static friction substantially the same as its coefficient of dynamic friction.
2. (Previously Presented) A protection sheeting as claimed in claim 1 wherein the material has a coefficient of friction less than 0.4.
3. (Currently Amended) A protection sheeting as claimed in claim 1 [[or 2]] wherein the material is woven.
4. (Currently Amended) A protection sheeting as claimed in claim 1 ~~any of the preceding claims~~ wherein the linear density of the material is between 1000 and 40 decitex.
5. (Currently Amended) A protection sheeting as claimed in claim 4 wherein the linear density is [[470,]] 350 ~~or 50~~ decitex.
6. (Currently Amended) A protection sheeting as claimed in claim 4 [[or 5]] wherein the weight of the material is between 200 and 50 gm/m².
7. (Currently Amended) A protection sheeting as claimed in claim [[4]] 5 wherein the material's weight is 180 gm/m² for the 350 decitex material ~~and about 62 gm/m² for the 50 decitex material.~~
8. (Currently Amended) A protection sheeting as claimed in claim 1 ~~in any one of claims 1 to 7,~~ formed as a bootie with one or more layers of the material.

9. (Previously Presented) A protection sheeting as claimed in claim 8 wherein the bootie is formed without a toe.

10. Cancelled without prejudice or disclaimer.

Please add the following New Claims:

11. (New) A protection sheeting as claimed in claim 2 wherein the material is woven.

12. (New) A protection sheeting as claimed in claim 2 wherein the linear density of the material is between 1000 and 40 decitex.

13. (New) A protection sheeting as claimed in claim 3 wherein the linear density of the material is between 1000 and 40 decitex.

14. (New) A protection sheeting as claimed in claim 4 wherein the linear density is about 470 decitex.

15. (New) A protection sheeting as claimed in claim 4 wherein the linear density is about 50 decitex.

16. (New) A boot for covering a medical dressing located on a patient's foot comprising:

- a) a housing for enveloping a foot;
- b) a first and second end located about said housing such that said first end is enclosed forming a toe and said second end includes an opening for receiving a foot;
- c) a collar surrounding said opening at said second end;
- d) an external seam securing the housing of said boot from said first end to said second end;
- e) a slice extending from said opening at said second end to a midsection of said boot;
- f) a plurality of straps encompassing said slice for substantially closing and securing the

slice about a foot; and

- g) a medical protection sheeting making up the material for said housing, wherein said sheeting is formed from a low frictional material having a coefficient of static friction substantially the same as its coefficient of dynamic friction.

17. (New) The boot of claim 16, wherein said boot is formed without said toe.

18. (New) The boot of claim 16, wherein said sheeting has a linear density between 1000 and 40 decitex.

19. (New) The boot of claim 16, wherein said sheeting has a linear density of about 50 decitex.

20. (New) The boot of claim 16, wherein said sheeting has a coefficient of friction less than 0.4.

21. (New) The boot of claim 20, wherein said material is woven.

22. (New) The boot of claim 19, wherein the weight of said sheeting is between 200 and 50 gm/m².